

CSRT Series

Wide Temp Monitors



Sunlight Readable Touchscreen

Displays Designed for the Vehicle and Heavy Machinery Industries.



10" Display
CSRT-101W



12" Display
CSRT-121



15" Display
CSRT-156W

FEATURES

- IPS Wide Viewing Angle
- Bezel-Free Design
- IP65 Front Bezel
- IP66 Front Bezel Compliant
- VGA/DP/HDMI
- USB Port for Touch
- DC 12V Power Input (Optional DC9~36V)
- Optional 256 Levels Dimming
- Optional OSD in Front Right Side
- Optional IEC-60945 Compliance
- Optional 1000~1500 nits High Brightness
- Optional M12 Metal Connector Backside OSD Buttons
- Optional Anti-UV / Irradiation
- Optional Color Calibration / ECDIS



Seatronx Part Numbers:	CSRT-101W	CSRT-121	CSRT-156W
Max. Resolution	1280*800	1024*768	1920*1080
Contrast Ratio	800 : 1	700 : 1	800 : 1
Max. Color	16.7 M	16.2 M	16.2 M
Luminance (cd/m2)	400 nits Optional backlight 1000~1500 nits	500 nits Optional backlight 1000~1500 nits	450 nits Optional backlight 1000~1500 nits
View Angle	85/85/85/85	80/80/80/80	85/85/85/85
Touch Screen	10.1" P-cap USB interface	12" P-cap USB interface	15.6" P-cap USB interface
Power Input	DC 12V with DC 12V adapter by 3-Pin Terminal Block	DC 12V with DC 12V adapter by 3-Pin Terminal Block	DC 12V with DC 12V adapter by 3-Pin Terminal Block
Mounting	Panel Mount; VESA Mount 75x75/100x100	Panel Mount; VESA Mount 75x75/100x100	Panel Mount; VESA Mount 75x75/100x100
Operating Temp	-40 ~ 80 °C	-40 ~ 80 °C	-40 ~ 80 °C
Storage temp	-40 ~ 80 °C	-40 ~ 80 °C	-40 ~ 80 °C
OSD Function	1. Power 2. Backlight Up 3. Back light Down 4. Home 5. Status switch 6. LED for Day, Noon and Night status (Optional Only for ECDIS)	1. Power 2. Backlight Up 3. Back light Down 4. Home 5. Status switch 6. LED for Day, Noon and Night status (Optional Only for ECDIS)	1. Power 2. Backlight Up 3. Back light Down 4. Home 5. Status switch 6. LED for Day, Noon and Night status (Optional Only for ECDIS)

NOTE: 17", 19" and 24" options available. Consult factory for details

CSRT Series Sunlight Readable Touch Screen Displays	
Part #:	Description :
CSRT-101W	10.1" 1280x800 Sunlight readable touch screen display, 12VDC
CSRT-121	12" 1024x768 Sunlight readable touch screen display, 12VDC
CSRT-156W	15.6" 1920x1080 Sunlight readable touch screen display, 12VDC



USA: (800) 607-1460
 TEL: (772) 418-5035
 EMAIL: Info@Seatronx.com
 WEBSITE: www.seatronx.com