



# IND-24W

## LED- Sunlight Readable Industrial/Marine LCD Monitor

This product features the latest in LCD technology with 900 nit LED backlights rated at 100,000 hours life.

This product features optically bonded anti -reflective glass, perfect 1000:1 dimming, DVI, VGA, HDMI and Mil Spec. OSD controls.

### Features

- 24.07" TFT LCD
- 1,920 X 1,200 Resolution(WUXGA)
- 10 to 38VDC Power Input, AC/DC Brick Power Supply Included
- Applications: In-Outdoor, Marine, Air craft, Vehicles.

### Specifications

LCD Type	TFT Active Matrix LCD (2.07 Million colors)
Display Size	24.07"
Resolution	1,920 x 1,200(WUXGA)
Contrast Ratio	1,000:1
Brightness	LED Backlight Type- 900 nit(min.)
Panel Surface	Anti-Glare Coating with Tempered Glass
Inputs	DVI, VGA, HDMI(With PIP/POP)
Mounting Options	VESA / Flush/U-Bracket mounted
View Angle	178(H) 1708(V)
Response Time	14m/sec
Light Source	Light Emitting Diodes
Input Voltage	10 to 38VDC Power Input, AC/DC brick power supply included
Power Consumption	60W
Out-dimensions	23.4"(W)x16.61"(H)x2.56"(D), 595(W)x422(H)x65(D)mm
Operating Range	-0C ~ 50C
Cases Color	Black ,Dark Gray
IP Rating	Front Side:IP65, Rear Side:IP32
Warranty	2 yrs
Dimming Range	1000:1 (dimming control to dark to full bright)
Weight	22 LBS(10Kg)



Our Vision is Your Vision

SEATRONX, LLC  
PO Box 1713 • Hobe Sound FL 33475  
(772) 418-5035 • info@seatronx.com  
[www.seatronx.com](http://www.seatronx.com)