

Crane and Equipment Camera System

Total Solution for All Cranes
Full HD! Wireless!
30X Optical Zoom
Max 300m Wireless Transmission



DISTRIBUTED BY



USA: (800) 607-1460
TEL: (772) 418-5035
EMAIL: Info@Seatronx.com
WEBSITE: www.seatronx.com



1080P 10" Wireless Monitor	
Color LCD Display	10.1 inch IPS Screen
Wireless Receiver	Built-in 2.4G Wireless Receiver
Picture Mode	Single screen/dual screen/three-screen/four-screen
Working Frequency	2400~2483.5MHZ
Recording Function	Maximum support 128GB SD card
Recording File	MP4 format
Receiving Sensitivity	≤ -86 dB
Receiving Distance	Open ≤ 300m
Frequency Hopping Channel	80
Resolution	1024(H) X 600(V)dot
Color System	PAL/NTSC (AUTO)
Brightness (cd/m2)	600
Load Dump	ISO16750-2 Standard(24V Us=174V,Ri= 4Ω,td=350ms)
Anti-vibration Grade	5G
Operating Temperature	-20℃ to +70℃
Storage Temperature	-30℃ to +80℃
Operating Voltage	DC8-32V
Dimensions	(L x W x T) (276 x 185 x 66.5mm)
1080P Digital Wireless 30x Zoom Camera	
Image Sensor	1/2.8" Color DSP
Wireless Transmission	Built-in 2.4G digital wireless transmitter
Transmit Power	18dBm
Resolution	1080P
Effective Pixels	1920(H)X1080(V)



Optical Zoom	30x
Focal Length	5.35 ~ 96.3mm
Aperture Value	F1.6 ~ F3.5
Horizontal Viewing Angle	64.1 ~ 3.6 degrees (Wide angle-telephoto)
Visual Distance	5-200 meters
Zoom Speed	About 3 seconds (Optical, wide-angle-telephoto)
Focus Mode	Auto focus
Day & Night Mode	IR-CUT automatic switching (Color daytime, black and white image at night)
Infrared Distance	50 meters (Built-in 4 high-power infrared lights)
Shell Material	Aluminum alloy, anti-wire rope buckle design
Mounting Brackets	Vertical gravity stainless steel bracket
Waterproof Level	IP69K
Operating Voltage	DC12V
Operating Temperature	-20℃ to +60℃
Storage Temperature	-30℃ to +70℃
Anti-vibration Grade	5G
Dimensions	220(W) x 90(H) x 90(D) mm
Mobile Rechargeable Power Supply	
Cell Type	Lithium polymer battery
Product Capacity	5000maH
USB Input (Support fast charge 3.0)	USB universal port (with protocol fast charge); 12V/1.5A (about 10.5 hours for full charge)
DC Output	DC12V/0.8A (DC5.5/2.1 male)
Charging Cycle Temperature	0°~+40°



Charge & Discharge Times	> 800 times
Discharge Working Temperature	-10°~+50°
Anti-ping Design	Design of anti-ping wire rope buckle
Strong Magnetic	Magnetic base installation (Built-in 11 strong magnets, front horizontal pull> 20kg, side pull> 8kg)
Waterproof Level	IP67
Anti-vibration Level	5G
Dimensions	148(W) x 88(H) x 45.5(D) mm

CRANECAM™ Wireless Crane 30X Zoom Camera System

Wireless portable safety crane camera system integrates the innovative battery technology with high-definition 1080P 30X zoom wireless cameras to reinvent a highly reliable cost-effective safety solution for cranes.

Kocchi's manufactures various types of construction camera systems, including tower cameras and crane cameras that offer crane operators with a wide angle view.



DISTRIBUTED BY



USA: (800) 607-1460
TEL: (772) 418-5035
EMAIL: Info@Seatronx.com
WEBSITE: www.seatronx.com